

TECHNICAL DATA SHEET



PETRATOP-L

Stone wool plates with a bright veil for thermal, sound absorption and fire protection

OFFICIAL DOCUMENTATION:

Declaration of Performances
Nr PTRL-DoP/MW/22/126

APPLICATION:

ceilings above garages
basements



PETRALANA S.A.
Konstytucji 74 Street
41-905 Bytom
Poland
+48 32 770 05 00
office@petralana.eu

PRODUCT CODE

PETRATOP-L MW-EN13162-T5-DS(70,90)-CS(10)0,5-WS-WL(P)-MU1-AW1,00

DECLARED THERMAL CONDUCTIVITY COEFFICIENT λ_D

$\leq 0,034[W/(mK)]$

DECLARED PARAMETERS

DECLARED PROPERTIES OF THE PRODUCT ACC. TO EN 13162:2012+A1:2015	SYMBOL	CLASS OR TOLERANCE	UNITS
Class for thickness tolerances	T	T5	-1 mm / +3 mm
			-1 % / +3 mm
Dimensional stability under 70 °C and 90% humidity	DS(70,90)	$\leq 1,0$	[%]
Compressive stress at 10% deformation	CS(10/Y)	0,5	[kPa]
Tensile strength perpendicular to faces	TR	NPD	[kPa]
Point load at 5mm deformation	PL(5)	NPD	[-]
Short time water absorption	WS	$\leq 1,0$	[kg/m ²]
Long time water absorption	WL(P)	$\leq 3,0$	[kg/m ²]
Water vapour transmission	MU	MU1	[-]
Air flow resistivity	AFr	NPD	[kPa s/m ²]
Reaction to fire	RIF	A1	Euroclass
Sound absorption	AW	1,00	[-]

DECLARED THERMAL RESISTANCE R_D

d [mm]	120	140	160	180	200	220	240	250	-	-	-	-	-	-	-	-
R_D [m ² K/W]	3,50	4,10	4,70	5,25	5,85	6,45	7,05	7,35	-	-	-	-	-	-	-	-

DIMENSIONS AND PACKING

FORMAT OF PLATES			PACKAGES			PALLETS			
Length	Width	Thickness	No. of plates in a package	Cover surface of a package	Volume of a package	No. of plates on a pallet	Cover surface of plates on a pallet	Volume of plates on a pallet	
[mm]	[mm]	[mm]	[pcs.]	[m ²]	[m ³]	[pcs.]	[m ²]	[m ³]	
1000	600	120	5	3,00	0,360	16	48,00	5,760	
		140	4	2,40	0,336	16	38,40	5,376	
		150	4	2,40	0,360	16	38,40	5,760	
		160	3	1,80	0,288	20	36,00	5,760	
		180	3	1,80	0,324	16	28,80	5,184	
		200	3	1,80	0,360	16	28,80	5,760	
		250	2	1,20	0,300	20	24,00	6,000	
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-